KOOB®

Dimmable:
0.1%-100%

DALI 2

LED Intelligent Driver (CV)

- Dimming range: 0~100%, LED start at 0.1% possible.
- 0-100% flicker-free, High frequency exemption level.
- Dimming interfaces: DALI-2, Push DIM,0-10V,1-10V, 10V PWM,RESISTANCE DIM
- High Efficient driver: PF>0.96, THD<10%
- Over load / Over temp. / Short circuit / Over voltage protection, recover automatically.
- Suitable for internal lights application for Ⅰ/Ⅱ/Ⅲ.
- Up to 50000-hour life time.



0-10V
1-10V
10V PWM
Resistance DIM
DALI-2
PUSH DIM

PF>0.96

THD<10%

Flicker-free
IEEE 1789
High frequency exemption level

SELV IP20

0-10V 1-10V DIM | PWM Digital Dimming | Resistance DIM | 0.1% Depth Dimming | DALI Push DIM | Over-heat Protection | Short Circuit Protection | Over Load Protection | V Over voltage protection

Specification

Model		YSD-200WUDL-12D	YSD-200WUDL-24D	YSD-200WUDL-36D	YSD-200WUDL-48D
OUTPUT	Output voltage	12VDC	24VDC	36VDC	48VDC
	Output voltage range	12VDC±0.3VDC	24VDC±0.6VDC	36VDC±0.6VDC	48VDC±0.6VDC
	Output current	Max 16.7A	Max 8.3A	Max 5.56A	Max 4.17A
	Output power	Max 200W			
	Output power range	0~200W			
	With or without strobe	No strobe			
	Dimming range	0~100%, dimming depth: Max. 0. 1%			
	Ripple & Noise	≤150mV	≤240mV	≤360mV	≤480mV
	PWM frequency	4-16Khz			
INPUT	Dimming interface	DALI-2 /PUSH DIM/0-10V/1-10V/10V PWM/RESISTANCE DIM(0-100K)			
	Input voltage	100-264Vac			
	Frequency	50/60Hz			
	Input current	2.4~0.8A			
	Power factor	PF>0.96/230Vac, at full load			
	THD	≤10% at 230Vac, at full load			
	Efficiency (typ.)	93%	94%	94%	94%
	Inrush current(typ.)	Cold start 60A at 230Vac			
	Control surge capability	L-N:1KV			
	Leakage current	Max. 0.5mA			
ENVIRONMENT	Working temperature	ta: -25°C ~ 50°C tc: 90°C			
	Working humidity	20 ~ 95%RH, non-condensing			
	Storage temp., humidity	-40°C ~ 80°C, 10~95%RH			
	Vibration	10~500Hz, 2G 12min./1cycle, period for 72min. each along X, Y, Z axes.			
PROTECTION	Overtemperature	Protection type:Shut down o/p voltage,re--power on to recover			
	Over voltage protection	The no-load voltage is greater than 120%~150% rated output voltage.Shut down the output and It can be automatically restored after the fault is eliminated ,			
	Short circuit protection	Protection type: 1. When the first level short-circuit protection is triggered, the fault will recover automatically after 3 seconds. 2. When the second-level short-circuit protection is triggered, the power needs to be turned on again after the fault is eliminated			
SAFETY & EMC	Withstand voltage	I/P-O/P: 3750Vac			
	Isolation resistance	I/P-O/P: 100MΩ/500VDC/25°C/70%RH			
	Safety standards	IEC/EN61347-1, IEC/EN61347-2-13			
	EMC emission	EN55015, EN61000-3-2 Class C, IEC61000-3-3			
	EMC immunity	EN61000-4-2,3,4,5,6,8,11 EN61547			
	Strobe test standard	IEEE 1789			

Dimensions

Unit: mm



Wiring diagram

DALIConnection Mode



PUSH DIMConnection Mode



✻ The priority of the dimming interface is: 0-10V first, second DALI, last is Push DIM

Push DIM



Reset switch

On/off control: Short press.

Stepless dimming: Long press.

With every other long press, the brightness level goes to the opposite direction.

Dimming memory: Go to the brightness level adjusted previously when lights are turned on.

KOOB®

Relationship diagrams



YSD-200WUDL-12D



YSD-200WUDL-24D



YSD-200WUDL-36D



YSD-200WUDL-48D

Packaging Information

DIMENSION	265x39x24.8mm(LxWxH)
PACKING	273x45x33mm(LxWxH)
CARTON QUANTITY	30PCS
CARTON SIZE	355x285x155mm(LxWxH)
WEIGHT	390g±10gPCS

Temperature load curve



Flicker Test Form

IEEE 1789

Limit of Modulation in low risk area	
Waveform frequency of Optical output	limit (%)
$f \leq 8Hz$	0.2
$8Hz < f \leq 90Hz$	$0.025 \times f$
$90Hz < f \leq 1250Hz$	$0.08 \times f$
$f > 1250Hz$	Exemption assessment
Limit of Modulation in no effect area	
Waveform frequency of Optical output	limit (%)
$f \leq 10Hz$	0.1
$10Hz < f \leq 90Hz$	$0.01 \times f$
$90Hz < f \leq 3125Hz$	$(0.08/2.5) \times f$
$f > 3125Hz$	Exemption assessment (High frequency exemption)



* No further notice if any changes in the manual. Product function depends on the goods. Please feel free to contact your supplier if any question.